

541980

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/064005 A2

- (51) International Patent Classification⁷: **G08C**
- (21) International Application Number:
PCT/IB2003/006279
- (22) International Filing Date:
15 December 2003 (15.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
03100052.4 14 January 2003 (14.01.2003) EP
- (71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).
- (71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DEPPE, Carsten**

[DE/DE]; c/o Philips Intellectual Property & Standards
GmbH, Weisshausstr. 2, 52066 Aachen (DE). **DÜR-
BAUM, Thomas** [DE/DE]; c/o Philips Intellectual
Property & Standards GmbH, Weisshausstr. 2, 52066
Aachen (DE). **SAUERLÄNDER, Georg** [DE/DE]; c/o
Philips Intellectual Property & Standards GmbH, Weis-
shausstr. 2, 52066 Aachen (DE).


(74) Agent: **MEYER, Michael**; Philips Intellectual Property &
Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

[Continued on next page]

(54) Title: **CIRCUIT ARRANGEMENTS AND METHODS FOR A REMOTE CONTROL RECEIVER HAVING A PHOTODIODE**



(57) Abstract: A control unit (2) of a remote control receiver sets the forward or reverse direction operating mode of the photodiode (1) as a function of the useful signal level of its output signal, and to be precise, during standby, the photovoltaic operating mode (forward mode), since in this mode no external bias current is required. If the useful signal level of the photodiode (1) exceeds a predefined threshold, the reverse mode is set, and this brings with it a higher sensitivity. A series circuit (A) of a number of identical photodiodes DA1 DAn in the forward mode allows the realization of a controlled current source (6) having a transistor (T), since the permissible diode voltage (Ud) of the overall arrangement may have n times the value of the operating voltage of an individual photodiode. Thus at the same time the voltage across the individual diodes can be set to a very low value and a favorable operating range for the current source can be set. The possible sensitivity of the receiver module having diodes in this operating mode can thereby be considerably increased.

WO 2004/064005 A2



SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*